


Stabilizing frame 55 inch



082.5190 Smart Rental Frame - 46 inch Stabiliser for flying

The coupling frames and bracket frames are attached to this frame, due to which it offers additional support during flying. The set enables the installer to choose between: Mounting on the floor and attaching the matrix to the truss when configuration is complete; working from bottom to top. Or attaching the screens per row to the truss; working from top to bottom. With wall installation, the bracket frames fitted with a screen specific bracket, are screwed to the wall. Through special draw latches they are fastened to neighbouring frames. When installing on the floor the floor frames are levelled on their location, coupling frames are fastened to these frames with camlocks, after which the bracket frames incl. screen specific brackets are connected with draw latches. When planning to fly the VideoWall in the truss, the floor frames are replaced by stabilizer frames and at the top of the coupling and bracket frames special fly sets are attached. These fly sets include a dept adjustment to level the VideoWall in the truss. The screen specific brackets include four keyholes in which the display (fitted with 4 coupling bolts) is hung. These innovations result in an impressive VideoWall which is now even easier and more precise to install then before.

Stabilizing frame 55 inch

Features

Weight: 7.10 kg

Colour: Black

Screen position: Landscape, Portrait

Inch range: 46 inch (Seamless)

Mobile / fixed: Fixed

